



- ❖ Vin cap is PVC Cap made from specially formulated Poly Vinyl Chloride material.
- ❖ Push-on type application.
- ❖ Ensures perfect protection to cable ends from weathering, moisture and contamination.
- ❖ Quick and easy installation without any tools. No skill is required.
- ❖ Extremely economical and cost effective compared to Heat Shrink End Caps.
- ❖ Caps of varying lengths & thickness can be made with no tooling charge.
- ❖ Will not Crack or Split like Low Density Polyethylene.

SELECTION CHART

All dimensions are in mm.

D	L	D	L	D	L	D	L
4	25	30	40	62	50	140	63
6	25	31	40	64	50	152	63
7	35	32	40	65	50	168	63
8	35	34	40	68	50	191	63
9	40	37	40	70	50	203	63
10	40	38	40	73	50	254	63
12	40	40	40	75	50	305	63
13	40	41	40	77	50	356	63
15	40	42	40	80	60	406	63
16	40	44	40	83	60	457	63
17	40	45	40	85	60	508	63
18	40	47	40	88	60	610	63
19	40	48	40	90	60	660	63
20	40	50	50	95	60	711	63
22	40	51	50	100	60	762	63
24	40	52	50	105	60	813	63
25	40	53	50	110	60	914	63
26	40	55	50	115	60		
27	40	57	50	118	60		
28	40	60	50	127	63		

NOTE: Customised size, length & colours available

TECHNICAL SPECIFICATIONS :

Test Description	Recorded Value	Test Method
Dielectric Strength	12 KV/mm. (min.)	ASTM D149
Tensile Strength	12 N/mm ² (min.)	ASTM D638
Elongation	350 % (min.)	ASTM D638
Density	1.23 gm/cm ³	ASTM D792
Hardness	65 ± 5 shore A	ASTM D2240
Continuous Operating Temp.	-20°C to 115°C	IEC 216
Flammability	Pass	UL 94-V0



